



Gunnebo ModuleGuard-VD

Grade II–IV certified burglary-resistant vault doors

- ModuleGuard security enclosures are certified Grade II–IV by ECB•S in accordance with the EN 1143-1 certification for burglary resistance
- A range of attack tools were used to test the level of resistance, from basic tools, such as drills and sledgehammers, to more sophisticated thermal and electrical equipment, like the oxyacetylene torch.
- Possible application areas: reinforced protection for cash-counting rooms, archives, storerooms (for weapons, pharmaceuticals), ATMs, etc.
- A series of high-security locking options is available
- The exterior of the enclosure can be painted or finished with decorative panels. Prepainted or galvanised versions available as an option

Gunnebo ModuleGuard-VD

Product Specifications

Clear Opening Height (mm)	Clear Opening Width (mm)	Thickness (mm)	Net Weight (kg) Grades II & III	Net Weight (kg) Grade IV
2055	750	185	690	780
2055	900	185	830	930
2055	1050	185	970	1090
2055	1200	185	1110	1240
2055	1350	185	1250	1400
2055	1500	185	1380	1550

Lock options

Key lock

- Kaba Mauer Praetor 70079 (Class B)

Combination lock

- S&G 6731 (Class B)

Electronic locks

- KelNet-DS (Class B, C, D)
- SafeLock (Class B, C, D)

